

## Tiered Web Site with Web-Tier Admission Control Based on Utilization Data Generated on Application Tier

### [0001] BACKGROUND OF THE INVENTION

5 [0002] The present invention relates to computers and, more particularly, to “host” computer networks that respond to requests from external “client” computers. A major objective of the present invention is to enhance the quality of service associated with a host site on the World Wide Web.

10 [0003] Much of modern progress is associated with the development of computers and the Internet, which permits computers to communicate worldwide. Several protocols exist by which a host site, which may comprise one or more “server” computers, receives and processes messages from a number of  
15 other computers (“clients”). For example, HTTP (HyperText Transfer Protocol) is a communications protocol used on the World Wide Web to enable users to navigate within and among host sites.

[0004] Messages can usually be grouped into sessions, with each session having one or more related messages. For example, a  
20 session can consist of a message requesting information over the World Wide Web, and an associated response. Alternatively, a multiple-message session can consist of a commercial transaction, with related messages respectively used to locate within a web site a precise product, submit an order or billing and shipping  
25 information, and convey a confirmation of sale to a particular client. Whether a host is to process just a single message or a series of

related messages, it is usually important to quickly, accurately, and completely service each message and each session.

[0005] The term "quality of service" refers to a host's ability to respond quickly to individual messages and to complete sessions.

5 As a particular host becomes more popular, and therefore receives more messages, the host's processing resources can become stretched. For example, due to heavy traffic, a host may not be able to respond to a message at all, or the host may not provide a timely response (which can cause a client to "time-out" with an error or the

10 impatient user to resend the message). Poor quality of service can have significant impact, as users may become frustrated and simply give up trying to reach a particular host, and the sponsor of the host may lose sales or fail to communicate needed information to some clients.

15 [0006] Quality of service can be improved by adding processing capacity and by implementing admissions control. Different approaches to increasing capacity are discussed further below. In many cases, it is cost effective to provide sufficient capacity to handle all messages most of the time, while relying on

20 admissions control for peak demand situations. Even where additional hardware resources can be added on demand, peak usage can occur too suddenly for the additional capacity to be operational; the time from the spike being identified to the time additional capacity is available can be hours to days for manual operations and

25 many minutes to hours for automatic or semi-automatic operations. During this time, admission control is often the best alternative to handling an immediate spike in usage, especially when the spike is short lived and far higher than the site's demand growth trend.

[0007] Admissions control involves selectively admitting and rejecting messages so that the messages that are processed are handled promptly and reliably. Intelligent admissions control can prioritize messages to advance the purposes of the host site. For example, messages associated with ongoing sessions can be given priority. U.S. Patent 6,006,269 to Phaal discloses a system in which admission determinations are made on a session basis and in which non-admitted messages are deferred with a higher priority level rather than rejected outright. Thus, opportunities associated with non-admitted messages are not necessarily lost.

[0008] Preferably, the admissions decisions are based on utilization data gathered by the host site. All messages can be admitted when resource utilization is low. As it increases to potentially problematic levels, admissions can become increasing selective. However, since there is a potential detriment to the site whenever admissions control rejects or defers a message, admission control is not desirable on a steady-state basis. It is preferable that host-site capacity be able to process all messages most of the time

[0009] In general, quality of service can be improved by adding processing power to the host site. For example, in a single-server site, a less powerful server can be replaced with a more powerful server. An advantage of the single-server replacement approach is simplicity. A single computer handles all site functions. Programs running on that computer can handle message, monitor resources, and administer admissions control.

[0010] On the other hand, there are limits to the single-server approach. At the high end, where the limits of available technology

are pushed, fractional increases in power are quite costly. Furthermore, when the single server is down, the entire site is down. Also, a replacement strategy can be wasteful if the replaced server is no longer used. In practice, most large sites use multiple servers.

5    [0011]       Similarly configured servers can be arranged in parallel. Servers can be added in parallel as needed to increase capacity. A load-balancing mechanism can be added at the front end to distribute messages among the parallel servers. However, the parallel servers need to be coordinated to ensure session integrity.  
10   Also, while admissions control can be done independently by each server, this results in messages being rejected by one server while there is ample capacity on another. It is not practical for the parallel servers to communicate with each other regarding each client request. While the coordination can, in principle, be  
15   performed at the load balancer, imposing additional processing requirements on the common node for all messages can result in an unacceptable performance bottleneck.

[0012]       A tiered host site overcomes many of the problems facing a multi-server host site. A typical tiered host site has a  
20   client-response tier (e.g., web tier using HTTP protocol) and an application tier. The application tier performs most of the resource-intensive work regarding the purpose of the site, while client-response tier typically provides the client interface. For example, the client-response tier can provide a web interface for a client,  
25   while the application tier handles e-commerce (electronic commerce) applications and maintains a database accessed by the applications. The application tier can manage sessions, tagging responses so that subsequent messages in the session can be identified as such. The client-response tier can use the session tags

to generate cookies and/or links associated with session-specific URLs to direct subsequent client requests to the proper application server.

[0013] Each tier can be expanded independently as required.  
5 Since the client-response tier manages the distribution of messages to the application tier, application tier servers can be differentiated by function. Capacity can be increased by activating (adding, turning on, or re-allocating) a server dedicated to the stressed function so that the additional resources are not wasted on  
10 underutilized applications.

[0014] The client-response tier can utilize parallel similarly configured servers. Coordination among the parallel servers is facilitated by the session tags added by the application tier. Expansion of the client-tier capacity is then readily achieved by  
15 adding additional servers in parallel. Alternatively, the client-response tier can be configured as a load-balancing hub supported by other servers dedicated to specific client-response functions, such as encryption and decryption. While the hub approach does place additional burdens on the common-node load balancer,  
20 session tracking is still managed primarily at the application tier. A hubbed client-response tier can be expanded efficiently by adding servers dedicated to a specific function that is over utilized.

[0015] In a tiered site, the admissions control function is typically assigned to the client-response tier since it provides the  
25 front-end interface to the client computer. The admission control function can monitor local resource utilization effectively on a per-server basis. The admission control function on the client-response tier can monitor response times associated with requests to the application tier as a measure of its resource utilization. The

resource utilization information about the client-response tier and the application tier then is used to determine the admissions control policy at any given time.

[0016] While the tiered host site ~~approach~~approach provides  
5 for efficient scaling and for effective admissions control, there is an insatiable demand for better performance. In particular, there is a demand for better admission control, since it is a software component that can, in principle, be upgraded less expensively than the host site hardware. What is needed is more effective admission  
10 control for a tiered host site.

#### [0017] SUMMARY OF THE INVENTION

[0018] The present invention provides a network host site in which admission control determinations are made on a client-response tier using resource utilization data collected on an  
15 application tier. The invention further provides for admissions-control determinations that are also made as a function of resource-utilization data collected on the client-response tier. In addition to being used for admissions determinations, the resource utilization data can be used to request an increase or decrease of active server  
20 resources.

[0019] The host site has distinct client-response and application tiers in that each ~~host-site~~host-site server is assigned to at most one of the tiers. Servers that only handle client interfacing are assigned to the client-response tier, while servers that run non-  
25 interfacing applications but do not handle client interfacing are assigned to the application tier. Servers that handle both non-interfacing applications and client interfacing are assigned to the client-response tier.

[0020] The invention provides for a variety of tier configurations. The client-response tier can be configured as a single server, as a set of parallel servers with a load-balancing front end, or as a set of specialized servers managed by a routing hub.

5 The application tier can have sub-tiers; for example, specialized application servers can be serviced by one or more database servers on a back end. Alternatively, the application tier can be arranged around a routing hub.

[0021] While application-tier performance can be assessed by  
10 the client-response tier, local application-tier resource monitoring has several advantages. First, the application server as a whole can be measured independently of the network and even other servers (such as the database). Also it allows for a disaggregated measure of an application's performance by resource components (for  
15 example, memory, CPU, I/O). Moreover, it allows each application to associate measurements with its own admissions classes and base them on session or even client identity.

[0022] Finally, resource monitoring can be customized on a per-server basis. Where multiple applications are running on the  
20 same server, customization can be implemented on a per-application basis. This allows for better optimization of application resources. For example, the application tier can generate resource utilization data in XML ("Extensible Markup Language) format with instructions to the client-response tier regarding interpretation and  
25 usage of the application-tier resource utilization data. These and other features and advantages of the present invention are apparent from the description below with reference to the following drawings.

[0023] BRIEF DESCRIPTION OF THE DRAWINGS

[0024] FIGURE 1 is a schematic diagram of a host site with parallel client-response-tier servers and connected to multiple clients in accordance with the present invention.

5 [0025] FIGURE 2 is a schematic diagram of the host site of FIG. 1 indicating internal communications paths and scalability options.

[0026] FIGURE 3 is a flow chart of a method of the invention implemented on the host site of FIG. 1.

10 [0027] ~~FIGURE 4 is a schematic diagram of a host site with a hub-based client-response tier and connected to multiple clients in accordance with the present invention.~~ An alternative embodiment is described but not illustrated.

[0028] DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0029] In accordance with the present invention, a host site  
15 AP1 communicates with client computers 11 over the Internet, indicated by a connection 13, as shown in FIG. 1. In this case, host site AP1 is an e-commerce site, and more specifically a flight-scheduling and reservation-handling site. More generally, the invention provides for host sites with a wide range of purposes.  
20 The host site is divisible into an application tier 15 and a web tier 17. In FIG. 1, client computers are depicted as part of a client tier 19. This is a conceptualization from the perspective of the host site and does not imply any special relationship among the client computers other than the ability to communicate with host site AP1.

25 [0030] The host-site hardware is shown in greater detail in FIG. 2. Web tier 17 has three active servers WS1, WS2, WS3, and a



load balancer 21. In periods of high demand, host site AP1 can activate up to three additional servers WS4, WS5, and WS6. Application tier 15 includes a database server AS1 and two front-end application servers AS2 and AS3, while an additional  
5 application server AS4 can be activated when additional resources are required. Servers WS4, WS5, WS6, and AS4 are normally inactive or used elsewhere in order to save costs. The relatively greater expandability of the web tier (indicated by having three servers in reserve versus one for the application tier) corresponds to the  
10 greater computing power and state maintenance normally required of the application servers, and thus the greater expense involved in adding servers to the application tier.

[0031] Application-tier servers, may, but need not, run the same software. For example, application server AS1 runs a database  
15 program that organizes information regarding flight schedules. Application server AS2 runs a flight scheduling application, while application server AS3 runs a flight reservation application. In times of high demand, application server AS4 can provide additional capacity for the flight-reservation function. Moreover, each  
20 application server can run multiple applications, some of which may run on only one application server, some of which may run on all application servers, and some of which may run on more than one but not all application servers. However, the application servers do not run the web-serving applications that interface directly with  
25 client tier 19.

[0032] Web servers WS1, WS2, and WS3, as well as the other web servers when active, run respective copies of the same software. Each runs a web serving application that provides the main interface to browsers running on client computers 11. Load

balancer 21 distributes client requests in round-robin fashion to the active web servers. In addition, each server can run one or more application programs other than web servers. However, the more complex application programs are run on the application-tier  
5 servers.

[0033] The common functions of servers on web tier 17 are shown in FIG. 1. Client requests are received at an admission control gateway 23. Gateway 23 initially determines whether or not the request is encrypted. If it is, it is decrypted at encrypt/decrypt  
10 function 25. Once the request is decrypted or if it was not encrypted, admission control gateway 23 determines whether to pass it on to (software) client-request processor 27, or to deferral manager 29. The decision is made as a function of the programming of admission control gateway 23 by deferral  
15 manager 29.

[0034] In the event the request is passed to it, client-request processor 27 determines whether it can respond to the request using local (web-tier-server) resources, or whether it needs to forward the request to application tier 15. In the former case, a  
20 client response can be generated in accordance with the client browser protocol (e.g., HTTP). The client response is passed to admissions control gateway 23. If encryption is required, admissions control gateway 23 passes the client-response to encrypt/decrypt function ~~27-25~~ and forwards the encrypted result  
25 to the client that made the request.

[0035] If the client request cannot be met locally, ~~client request~~ client-request processor ~~25-27~~ formulates an application request for an application processor 31 in the form of software running on application tier 15. Since not all servers of application

tier 15 run the same applications, client-request processor 25-27 must direct the application request to the appropriate server and application. If that target application is running on more than one application-tier server, client-request processor 25-27 must  
5 determine which of those servers to direct the application request to. Generally, requests associated with the same session are directed to the same application server. Otherwise, a selection can be made based on unused capacity, or more simply on a round-robin basis.

10 [0036] Some application requests can require processing on more than one server. For example, a request for flight-schedule information may require a flight-schedule application on server AS2 (FIG. 2) to access database server AS1. However many application servers are involved, an application response is generated at  
15 application tier 15 in response to the application request. The application tier can tag the application response with session identification information so that subsequent client requests in the same session can be correlated.

[0037] The application response is forwarded from application  
20 processor 31 to the client-request processor 2527. Typically, the application response is transmitted to the web-tier server that generated the corresponding application request. Alternatively, the selection of web-tier server for the application response can be selected on some other basis, e.g., round robin. Once client-request  
25 processor 25-27 receives an application response, it generates a client response, treating it in the manner described above for ~~locally-answered~~locally answered client requests.

[0038] Client-request processor 25-27 can use the session identification information to generate a cookie or a unique URL.

This URL can be communicated in the form of a web page link that generates a new client request with the session information embedded. This enables a web-tier server to route a subsequent message in a session to the appropriate application-tier server.

5    **[0039]**       Each application-tier server has a resource monitor 33. The parameters 35 to be monitored can be selected, but typically CPU usage is one parameter that is monitored. The parameter values determined through this monitoring are forwarded from the resource monitor to the deferral manager 2729. The resource  
10   monitor 33 of each application server forwards this data to every web-tier deferral manager 2729. The deferral manager 27-29 uses this information to determine the response of gateway 23 to client requests.

15   **[0040]**       Concurrently, the resource parameters associated with the web tier can be monitored. To this end, a web-tier resource monitor 37 on each web-tier server monitors usage including client-request processing and encryption and decryption activity. Note, the web-tier resource utilization data for each web-tier server can be provided to load balancer 21 (FIG. 2) so that it can take web server  
20   utilization data into account when distributing client requests.

25   **[0041]**       Depending on the programming, deferral manager 29 can command gateway 23, in the alternative to admit all requests, admit no requests, admit only requests associated with on-going sessions, or admit requests according to some more complex criteria. Non-admitted requests can be forwarded to the deferral manager. The deferral manager can assign a time for a client to resubmit the request. The deferral message is tagged so that a request in compliance with the deferral message is given preferential treatment at gateway 23. For example, resubmitted

requests can be admitted while new requests are deferred. The deferral time can be set as a function of resource utilization. In addition to controlling admission criteria, the deferral manager can send a request to a resource manager on the application tier to  
5 increase (or decrease) available resources.

[0042] A method M1 of the invention practiced in the context of host site AP1 is flow charted in FIG. 3. Method M1 includes two processes, a request-handling process P1 and a resource-utilization process P2. Request-handling process involves client tier 19, and  
10 the two host-site tiers: web tier 17, and application tier 15.

[0043] An illustrative sequence for request process P1 begins with a client sending a request at step S1. Load balancer 21 (FIG. 2) receives this request and allots it on a round robin basis, taking into account web-tier resource-utilization data, at step S2 to a web-tier  
15 server, e.g., server WS1. The gateway for the receiving server can either admit or defer this request. In this illustrative sequence, the request is deferred at step S3. In this case, deferral manager 29 generates and transmits to the client a deferral message indicating when the client can resubmit the request.

20 [0044] The client resubmits the request by clicking a link in the deferral message at step S4. Load balancer distributes this 2<sup>nd</sup> request to a web-tier server at a second iteration of step S2. In general, the deferred request is admitted at step S5.

[0045] Unless the client-request processor of the web-tier can  
25 respond on its own, it generates an application request and transmits it to the application tier at step S6. Each web-tier server knows which applications run on which application-tier servers, so the request is directed to an appropriate application-tier server.

The receiving server generates an application response at step S7. The receiving server may access other application tier servers, including a database server, as necessary to formulate this application response. The application tier can tag the application response with session-identification information to keep track of sessions. Finally, the client-request processor generates a client response, using the session identification to generate a cookie or a unique URL that can be used in routing subsequent messages in a session.

10 [0046] The client response S8 may result ~~is-in~~ a further client request. Assuming this is a continuation of a session, the session is identified in the new request. This session information is ignored by the load balancer, but used by the selected web-tier server to direct a new application request to the appropriate application tier server.

15 [0047] Resource process P2 is concurrent with multiple iterations of steps S1-S8. At step R1, application tier resources are monitored at the application tier. For example, each application tier server can monitor its own resources. The monitor generates usage data at step R2. This data is transferred to the web tier and used to generate deferral criteria at step ~~S3~~R3. The deferral criteria are used at the web tier to determine which requests are admitted (at step S5) and which steps are deferred (at step ~~S3~~R3).

25 [0048] In host site AP1, the web tier is arranged with servers operating in parallel. The invention provides for alternatives to the parallel web-tier arrangement. For example, the web tier can be implemented on a single server. Furthermore, a multi-server web tier can differentiate servers by function, for example, as in an alternative host sites~~system AP2 of FIG. 4.~~

[0049] ~~Host-site AP2~~The alternative host-site interfaces with a an alternative client tier ~~419~~, which includes a number of client computers ~~411~~. ~~Host-site AP2~~The alternative host site includes an alternative application tier ~~415~~ and an alternative web tier ~~417~~.  
5 ~~Application~~The alternative application tier ~~415~~, which is similar to application tier 15 of host site AP1, includes an alternative application processing function ~~431~~, an alternative application-tier resource monitor ~~433~~, and alternative resource parameters ~~435~~. However, the alternative web tier ~~417~~ of the alternative host site  
10 ~~AP2~~ is quite distinct from the parallel arrangement of web tier 17 of host site AP1.

[0050] ~~Web~~Alternative web tier 417 comprises six servers ~~423, 425, 426, 427, 428, and 429~~. Servers ~~423, 425, 427 and 429~~Four of these servers are dedicated to specific functions that were shared by  
15 all servers in web tier 17 of host site AP1. ~~Server 426~~One of the other two alternative servers provides additional processing for the encryption/decryption function. ~~Queue~~The other alternative server is a queue manager 428 that adds a function of queuing client and application requests for serial routing by the alternative admissions  
20 control gateway ~~423~~.

[0051] ~~Admission~~The alternative admissions control gateway ~~423~~ of FIG. 4 performs the function of admission control gateway 23 and the load-balancing function of load balancer 21 of FIG. 2. It essentially acts as the load-balancing hub for the alternative web  
25 tier ~~417~~. It determines whether encryption or decryption is required and directs messages to one of the alternative encryption/decryption servers ~~425, 426~~, as required. It implements deferral policy as directed by the alternative deferral manager ~~429~~. It directs appropriate client requests to ~~client request~~client-request

processor 427. Client and application requests are referred to the  
queue manager 429 for ordered processing. The one function that  
is not routed through the alternative gateway 423 is the resource  
monitoring function, in which resource utilization data is  
5 transmitted directly to the alternative deferral manager server 429.

[0052] An advantage to the web-tier hub approach of the  
alternative host site AP2 is that scaling can be done function by  
function, as it has been with encryption and decryption. Functions  
that are not heavily utilized need not be expanded to new servers.  
10 On the other hand, functions can be combined on a server to avoid  
underutilization of hardware.

[0053] The present invention has applicability to network  
communications and e-commerce. The invention is scaleable to any  
number of servers and provides for a wide variety of tier  
15 architectures with varying numbers of subtiers. These and other  
modifications to and variations upon the present invention are  
provided for by the present invention, the scope of which is defined  
by the following claims.

[0054] What Is Claimed Is:



## CLAIMS

1       1. A host site comprising:  
2       an application tier that generates resource utilization data; and  
3       a client-response tier that performs admission control using said  
4       resource utilization data.

1       2. A host site as recited in Claim 1 wherein:  
2       said client-response tier has  
3             an admissions control gateway for receiving client requests  
4             from client computers;  
5             a deferral manager for making determinations concerning  
6             which of said client requests should be admitted for  
7             processing at least in part as a function of application-  
8             resource-utilization data;  
9             a client-request processor for processing client requests  
10            admitted for processing, said client-request processor  
11            generating application requests in response to at least some  
12            of said client requests, said client-request processor  
13            generating client responses in response to application  
14            responses received in response to said application requests;  
15            and  
16       said application tier has  
17            at least one application-tier server not in said client-  
18            response tier,  
19            an application processing function running on said server  
20            for responding to said application requests with said  
21            application responses, and  
22            a resource monitor for generating said application-  
23            resource-utilization data by monitoring utilization parameters  
24            on said server, said resource monitor communicating said  
25            resource-utilization to said deferral manager.

1       3. A system as recited in Claim 2 wherein said client-request  
2 processor transmits said client responses to said client computers  
3 in accordance with an http protocol.

1       4. A system as recited in Claim 2 wherein said client-response  
2 tier includes at least one client-response-tier server on which said  
3 deferral manager and said client-request processor run, said client-  
4 response-tier also having a client-response-tier resource monitor for  
5 generating client-response-tier resource utilization data as a  
6 function of parameters associated with said client-response-tier  
7 server, said client-response-tier resource monitor providing said  
8 client-response-tier resource utilization data to said deferral  
9 manager, said deferral manager making said determinations in part  
10 as a function of said client-response-tier resource utilization data.

1       5. A system as recited in Claim 4 wherein said deferral manager  
2 also generates requests to expand the processing capacity on said  
3 client-response tier.

1       6. A system as recited in Claim 2 wherein said deferral manager  
2 generates requests to expand the processing capacity on said  
3 application tier.

1       7. A system as recited in Claim 6 wherein said processing  
2 capacity is expanded by one or more of the following: increasing the  
3 number of servers, increasing the number of processors, increasing  
4 CPU entitlement.

1       8. A network hosting method for a host site having an  
2 application tier and a client-response tier, said application tier  
3 having at least one server not included in said client-response tier,  
4 said method comprising a client-response process and a resource-  
5 monitoring process,  
6       said resource-monitoring process involving  
7           a1) monitoring resource utilization at said application tier,  
8           a2) generating resource-utilization data at said application  
9 tier and transmitting said resource-utilization data to said  
10 client-response tier, and  
11       said request processing involving  
12           b1) receiving at said client-response-tier a client request  
13 from a client via a network,  
14           b2) making an admissions determination at said client-  
15 response tier whether said client request should be admitted  
16 immediately or deferred, said determination being made at  
17 least in part as a function of said resource-utilization data,  
18           b3) when said client request is admitted, sending an  
19 application request from said client-response tier to said  
20 application tier,  
21           b4) generating an application response at said application  
22 tier and transmitting said application response to said client-  
23 response tier, and  
24           b5) generating a client response as a function of said  
25 application response and transmitting said client response to  
26 said client via said network.

1       9. A method as recited in Claim 8 wherein at step b2) in the  
2 event a determination is made to defer admission of said client  
3 request, a notification is sent to said client to that effect via said  
4 network.

1       10. A method as recited in Claim 8 wherein at step b2, in the  
2 event a determination is made to defer admission, a request is  
3 generated to increase the processing capacity on said application  
4 tier.

1       11. A method as recited in Claim 8 wherein at step b2) said  
2 determination is also a function of resource-utilization data  
3 generated at said client-response tier.

1       12. A host site method comprising:  
2       generating resource-utilization data on an application tier; and  
3       using said data on a client-response tier to determine admission-  
4 control policy.

## ABSTRACT OF THE DISCLOSURE

An e-commerce web site has an application tier and a web tier, each with multiple servers. The application tier runs the resource-intensive functions germane to the site's purpose; while  
5 the web tier provides the primary interface for clients. The web tier implements admission control so that some requests can be deferred during periods of heavy traffic. In addition, the web tier can request additional web-tier and application-tier resources when they can be added cost effectively. The application tier monitors its  
10 own resource utilization and communicates resource-utilization data to the web tier. The web tier uses this application-tier resource-utilization data to determine its deferral criteria. In addition, the web-tier can monitor its own resource utilization and take the results into account in determining the deferral criteria. By  
15 monitoring application-tier utilization at the application tier rather than remotely at the web tier, more accurate and more flexible information is obtained, allowing for a better-optimized deferral scheme.